

REVERSIBLE WITH COOLANT SYSTEM AND TEMPORISED TAPPING.



Max drilling capacity on cast iron with pre-drilling hole	Ø 40 mm
Max drilling capacity on steel with pre-drilling hole(s235jr)	Ø 32 mm
Face milling cutter max	Ø 80 mm
End milling capacity	Ø 25 mm
Tapping capacity	Ø 22 mm
Spindle taper	CM 4
Spindle speed	(6) 75 - 1600 rpm
Spindle travel	130 mm
Spindle rotation	Dx - Sx
Quill	Ø 76 mm
Column	Ø 115 mm
Head tilt left and right	± 60°
Manual vertical feed division	0.02 mm
Distance spindle axis - column surface	260 mm
Distance between spindle nose and table	715 mm
Table dimensions	585 x 190 mm
Table slots	12 mm
Longitudinal axis	360 mm
Cross axis	250 mm
Base dimensions	648 x 412 mm
Base slot	14 mm
Motor	230 V 50 Hz 1,5 kW
Cooling pump	230v 50 Hz 0.4 KW

### Included

Self-locking chuck 1 - 16 B16  
Keyed chuck 1 - 13 B16  
Drill chuck shank MT 4 B16  
Spindle taper shank MT 4 Ø 27 mm  
Reduction sleeve MT 4/3  
Reduction sleeve MT 3/2  
Oilers  
Tie rod M16  
Service keys

<b>Overall sizes</b>	740 x 790 x 1960h mm
<b>Net weight</b>	355 kg
<b>Packaging dimensions</b>	830 x 760 x 1870 h mm
<b>Gross weight</b>	376,00 kg
<b>EAN Code</b>	8012667245368