

REVERSIBLE WITH COOLANT SYSTEM AND TEMPORISED TAPPING.



<b>Max drilling capacity on cast iron with pre-drilling hole</b>	Ø 40 mm
<b>Max drilling capacity on steel with pre-drilling hole(s235jr)</b>	Ø 32 mm
<b>Face milling cutter max</b>	Ø 80 mm
<b>End milling capacity</b>	Ø 25 mm
<b>Tapping capacity</b>	Ø 22 mm
<b>Spindle taper</b>	CM 4
<b>Spindle speed</b>	(12) 75 - 3200 rpm
<b>Spindle travel</b>	130 mm
<b>Spindle rotation</b>	Dx - Sx
<b>Quill</b>	Ø 76 mm
<b>Column</b>	Ø 115 mm
<b>Head tilt left and right</b>	± 60°
<b>Manual vertical feed division</b>	0.02 mm
<b>Distance spindle axis - column surface</b>	260 mm
<b>Distance between spindle nose and table</b>	715 mm
<b>Table dimensions</b>	585 x 190 mm
<b>Table slots</b>	12 mm
<b>Longitudinal axis</b>	360 mm
<b>Cross axis</b>	250 mm
<b>Base dimensions</b>	648 x 412 mm
<b>Base slot</b>	14 mm
<b>Motor</b>	400 V 50 Hz 1,1 - 1,5 kW
<b>Cooling pump</b>	400v 50 Hz 0.4 KW

### Included

Self-locking chuck 1 - 16 B16  
 Drill chuck shank MT 4 B16  
 Spindle taper shank MT 4 Ø 27 mm  
 Reduction sleeve MT 4/3  
 Reduction sleeve MT 3/2  
 Oilers  
 Tie rod M16  
 Service keys

<b>Overall sizes</b>	740 x 790 x 1960h mm
<b>Net weight</b>	355 kg
<b>Packaging dimensions</b>	830x760x1870 h mm
<b>Gross weight</b>	381,50 kg
<b>EAN Code</b>	8012667199548