

NEW BELT TENSION DEVICE, REVERSIBLE TABLE WITH INTEGRATED SLIDING VICE, DRILLING DEPTH READOUT, LED LIGHT INCLUDED. ELECTRICAL...



<b>Max drilling capacity on cast iron with pre-drilling hole</b>	Ø 32 mm
<b>Max drilling capacity on steel with pre-drilling hole(s235jr)</b>	Ø 28 mm
<b>Continuous drilling capacity</b>	Ø 20 mm
<b>Spindle taper</b>	CM 4
<b>Chuck sizes</b>	1 - 16 mm B18
<b>Spindle speed</b>	(12) 150 - 2450 rpm
<b>Spindle travel</b>	120 mm
<b>Quill</b>	Ø 62 mm
<b>Column</b>	Ø 92 mm
<b>Height</b>	1720 mm
<b>Distance chuck-column</b>	255 mm
<b>Distance between spindle nose and table</b>	700 mm
<b>Distance between spindle nose and base</b>	1220 mm
<b>Table dimensions</b>	460 x 425 mm
<b>Slot</b>	14 mm
<b>Vice</b>	210 x 165 mm
<b>Motor</b>	400 V 50 Hz 1,5 kW
<b>Net weight</b>	136 kg
<b>Dimensions</b>	780 x 460 x 1730 h mm
<b>Gross weight</b>	143,00 kg
<b>EAN Code</b>	8012667254230
<b>Packaging dimensions</b>	1420x660x350 h mm

**Included**

Keyless chuck 1 - 16 B18  
Drill chuck shank MT 4