

**INCLINABLE AND ROTATING TABLE. ELECTRICAL SYSTEM WITH SEPARATE 24V CIRCUIT FOR ON-BOARD MACHINE CONTROLS.**



<b>Max drilling capacity on cast iron with pre-drilling hole</b>	Ø 20 mm
<b>Max drilling capacity on steel with pre-drilling hole(s235jr)</b>	Ø 16 mm
<b>Continuous drilling capacity</b>	Ø 12 mm
<b>Chuck sizes</b>	1 - 16 mm B16
<b>Spindle speed</b>	(12) 280 - 2380 rpm
<b>Spindle travel</b>	80 mm
<b>Quill</b>	Ø 40 mm
<b>Column</b>	Ø 72 mm
<b>Height</b>	990 mm
<b>Distance spindle axis - column surface</b>	160 mm
<b>Distance between spindle nose and table</b>	435 mm
<b>Distance between spindle nose and base</b>	650 mm
<b>Table dimensions</b>	Ø 290 mm
<b>Motor</b>	230 V 50 Hz 0,65 kW
<b>Net weight</b>	48 kg
<b>Gross weight</b>	49,50 kg
<b>EAN Code</b>	8012667000073
<b>Packaging dimensions</b>	780x460x270 h mm

**Included**

Keyless chuck 1 - 16 mm B16  
Drill chuck arbor MT 2 B16