


UTILIZZATE PRINCIPALMENTE NEI TORNİ CON Lé™ OBIETTIVO DI STABILIZZARE I PEZZI LUNGI E SOTTILI, PIÙ SOGGETTI ALLA FLESSIONE O..



€190,00



Cono morse	2
A	L2 39 mm - D2-D3 16 mm - $\hat{I}\pm 60^\circ$ mm
B	L2 35,5 mm - D2-D3 16 mm - $\hat{I}\pm 75^\circ$ mm
C	L2 33 mm - D2-D3 16 mm - $\hat{I}\pm 90^\circ$ mm
D	L2 46 mm - D2-D3 16 mm - $\hat{I}\pm 60^\circ$ mm
E	L2 40 mm - D2-D3 25 mm / 10 mm - $\hat{I}\pm 60^\circ$ mm
F	L2 36 mm - D2-D3 16 mm / 10 mm - $\hat{I}\pm 60^\circ$ mm
G	L2 39 mm - D2-D3 20 mm / 16 mm - $\hat{I}\pm 60^\circ$ mm
Max rpm	5000 g/min
Portata max	45 kg
Peso lordo	1,32 kg
Dimensioni imballo	305x165x70h mm
Codice EAN	8012667244682



Valigetta



Temprato



9 Pcs



Acciaio



Rettificato